

DIK-5553 プッシュコーン(土壌硬度計) Push-Cone (Soil Hardness Meter)



作物根の伸張に対する土壌の抵抗性や、農業機械の作業性等を判定するためには土壌の硬度を知らせることが大切です。

プッシュコーンは平らに削った土壌面に垂直にコーンを押し込むだけで抵抗値が簡単に測定できます。測定原理は山中式土壌硬度計と同じです。

In order to predict a soil resistance to grow plants or for agricultural machines, it is important to determine the hardness of the soil. The Push-Cone can measure a resistance value of soil easily by pushing the cone vertically into the soil profile scraped evenly. Principle of measurement is the same as the soil hardness meter, Yamanaka type.

- ◎ 握りやすく、滑りません
- ◎ 測定器にスリットがないので土が入る心配がありません
- ◎ 小型軽量で携帯便利です
- ◎ 抵抗値は見えやすい直読式です
- ◎ The grip is easy to hold and is not slippery.
- ◎ Do not worry about the soil to come in the unit, because there is no slit as another type.
- ◎ It is convenient to carry because it is small and light.
- ◎ It is easy to read the resistance value of the soil.

◆◆仕様



測定範囲	0~40mm(0~49MPa)
コーン角度	25° 20'
バネ強度	78.4N/40mm
外形寸法	L225mm × φ 40mm
総重量	約370g(本体のみ250g)

◆◆Specifications

Measuring range	0~40mm(0~49MPa)
Cone angle	25° 20'
Strength of spring	78.4N/40mm
Outside dimensions	L225mm × φ 40mm
Weight	250g
Total weight	Approx.370g

畑の硬さ(X)	粘りと乾湿
~10mm	干ばつが心配
10~15mm	ちょうどよい
15~22mm	やや硬いが根は伸びる
22~24mm	根は少し入るが伸びが悪い
24mm~	根伸が入らない湿害が心配

Hardness of field(X)	Soil condition
~10mm	Fear of drought
10~15mm	Best condition
15~22mm	A little hard, but roots grow
22~24mm	Roots grow a little
24mm~	Roots don't grow. Fear of wet damage.

ダイキ 大起理化工業株式会社

〒365-0001 埼玉県鴻巣市赤城台212-8 Tel 048-568-2500(代) Fax 048-568-2505
西日本営業所

〒525-0032 滋賀県草津市大路2-9-1 Tel 077-567-1750(代) Fax 077-567-1755

Head Office Daiki Rika Kogyo Co., Ltd.

212-8 Akagidai, Kounosu-shi, Saitama, 365-0001 Japan.

Tel:+81-48-568-2500 Fax:+81-48-568-2505

Branch Office Daiki Rika Kogyo Co., Ltd.

Rn.603, 9-1 Oji 2-chome, Kusatsu, Shiga, 525-0032, Japan.

Tel:+81-77-567-1750 Fax:+81-77-567-1755

Internet : <https://www.daiki.co.jp/> E-mail : mbox@daiki.co.jp

取扱店

●仕様・外観は改良のため、予告なく変更することがあります。●カタログと、実際の商品の色とは、印刷の関係で多少異なる場合もございます。
●カタログ記載内容/2019年4月1日

The contents of this catalog are subject to change without prior notice.

19.04.5553